

<h1 style="margin: 0;">Installation & Maintenance Instructions</h1> <p style="margin: 0;">2-WAY DIRECT-ACTING SOLENOID VALVES REVISION "H" & "R"</p> <p style="margin: 0;">NORMALLY OPEN OR NORMALLY CLOSED OPERATION</p> <p style="margin: 0;">BRASS OR STAINLESS STEEL CONSTRUCTION - 1/8", 1/4", OR 3/8" PIPE THREADS</p>	<p style="margin: 0;">SERIES</p> <p style="margin: 0;">8262</p> <p style="margin: 0;">8263</p>
--	---

NOTICE: See Installation and Maintenance Instructions, I&M No. V_9575_R7-sec1 for detailed instructions.

MAXIMUM OPERATING PRESSURE DIFFERENTIAL FOR DC VALVES ONLY

Maximum Operating Pressure Differential For CatalogNumbers 8262H & 8263H DC Valves						
	At Maximum 40°C Ambient			At Maximum 55°C Ambient		
	Air-Inert- Gas [PSI]	Water [PSI]	Oil [PSI] 300 ssu	Air-Inert- Gas [PSI]	Water [PSI]	Oil [PSI] 300 ssu
8262H001	750	640	550	750	600	500
8262H002	130	110	95	120	100	90
8262H006	130	110	95	120	100	90
8262H007	130	110	90	120	100	85
8262H011	295	210	205	285	200	195
8262H012	750	640	550	750	600	500
8262H013	38	33	31	35	30	28
8262H014	235	160	160	215	150	145
8262H015	235	160	160	215	150	145
8262H016	165	130	130	155	120	120
8262H019	750	640	550	750	600	500
8262H020	235	160	160	215	150	145
8262H021	295	210	205	285	200	195
8262H022	130	110	90	120	100	85
8262H023	165	130	120	155	120	115
8262H036	38	33	31	35	30	28
8262H038	27	23	21	24	22	20
8262H079	965	745	720	920	700	675
8262H080	750	640	550	750	600	500
8262H086	235	160	160	215	150	145
8262H089	1500	1500	1500	1500	1500	1500
8262H090	27	23	21	24	22	20
8262H096	750	620	565	700	565	530
8262H099	1170	1145	945	1000	965	855
8262H105	275	275	235	250	250	225
8262H106	750	620	530	700	565	495
8262H107	1500	1500	1500	1500	1500	1500
8262H108	290	290	270	240	240	225
8262H109	610	410	410	600	410	400
8262H110	275	275	235	250	250	225
8262H111	72	60	55	67	53	52
8262H112	135	135	135	115	115	115
8262H113	95	75	75	85	72	70
8262H114	70	70	70	65	65	65
8262H174	275	275	235	250	250	225
8262H176	2000	2000	1725	1900	1900	1700
8262H177	290	290	270	240	240	255
8262H178	610	410	410	600	410	400

Maximum Operating Pressure Differential For CatalogNumbers 8262H & 8263H DC Valves						
	At Maximum 40°C Ambient			At Maximum 55°C Ambient		
	Air-Inert- Gas [PSI]	Water [PSI]	Oil [PSI] 300 ssu	Air-Inert- Gas [PSI]	Water [PSI]	Oil [PSI] 300 ssu
8262H180	750	620	530	700	565	495
8262H181	2000	2000	1725	1900	1900	1700
8262H182	290	290	270	240	240	225
8262H183	610	410	410	600	410	400
8262H185	275	275	235	250	250	225
8262H186	72	60	55	67	53	52
8262H187	135	135	135	115	115	115
8262H188	70	70	70	65	65	65
8262H200	1170	1145	945	1000	965	855
8262H202	65	63	63	55	54	54
8262H208	35	35	35	30	30	30
8262H210	25	25	22	22	22	20
8262H212	53	50	47	48	46	44
8262H214	1170	1145	945	1000	965	855
8262H230	53	50	47	48	46	44
8262H232	130	125	115	110	105	100
8262H277	610	410	410	600	410	400
8263H002	130	110	80	120	100	76
8263H003	165	130	110	155	120	105
8263H054	27	23	21	24	22	20
8263H115	275	275	160	250	250	150
8263H116	72	60	55	67	53	52
8263H117	95	75	75	85	72	70
8263H118	135	135	100	115	115	90
8263H119	38	33	31	35	30	28
8263H124	35	35	35	30	30	30
8263H191	275	275	160	250	250	150
8263H192	72	60	55	67	53	52
8263H193	135	135	100	115	115	90
8263H194	38	33	31	35	30	28
8263H196	27	23	21	24	22	20
8263H200	65	63	50	55	54	44
8263H206	70	70	70	65	65	65
8263H210	53	50	47	48	46	44
8263H232	130	125	85	110	105	75
8263H330	130	110	80	120	100	75
8263H332	70	70	70	65	65	65
8263H333	53	50	47	48	46	44

NOTES:

1. Suffix T (PTFE) valve maximum operating pressure differential is reduced by 25%.
2. Suffix MS valves are limited to maximum 750 PSI rating.